

View Online at <https://aerobasegroup.com/nsn/5306-01-315-3787>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.740 inches and 0.891 inches

**Fastener Length:**

Between 1.490 inches and 1.510 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.293 inches and 0.313 inches

**Width Between Flats:**

0.312 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

0.060 inches

**First Diameter From Head:**

Between 0.222 inches and 0.232 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.619 inches and 0.750 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

32 micro inches on grip and bearing surface of head; heat treated per pwa 586-3 on chamfered point and chamfer top of threads

**Material:**

Nickel alloy

**Material Specification:**

Pwa 96 cagec 77445 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0