NSN 5306-01-315-3787

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-315-3787 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.740 inches and 0.891 inches **Fastener Length:** Between 1.490 inches and 1.510 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.060 inches **First Diameter From Head:** Between 0.222 inches and 0.232 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.619 inches and 0.750 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Special Features:** 32 micro inches on grip and bearing surface of head; heat treated per pwa 586-3 on chamfered point and chamfer top of theads Material: Nickel alloy **Material Specification:** Pwa 96 cagec 77445 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-01-315-3787

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0