

View Online at <https://aerobasegroup.com/nsn/5306-01-315-4889>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.820 inches and 0.923 inches

**Fastener Length:**

Between 0.928 inches and 0.948 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.373 inches and 0.393 inches

**Width Between Flats:**

0.4375 inches

**Extended Washer Diameter:**

Between 0.552 inches and 0.572 inches

**Extended Washer Thickness:**

0.090 inches

**First Diameter From Head:**

Between 0.343 inches and 0.353 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.025 inches and 0.108 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Surface on grip and bearing surface of head 32 micrinches; threads and washer face coated pwa 550-3 agec 77445

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 7461 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0