NSN 5306-01-315-4889

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-315-4889 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.820 inches and 0.923 inches **Fastener Length:** Between 0.928 inches and 0.948 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.373 inches and 0.393 inches Width Between Flats: 0.4375 inches **Extended Washer Diameter:** Between 0.552 inches and 0.572 inches **Extended Washer Thickness:** 0.090 inches **First Diameter From Head:** Between 0.343 inches and 0.353 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.025 inches and 0.108 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity: Special Features:** Surface on grip and bearing surface of head 32 micrinches; threads and washer face coated pwa 550-3 agec 77445 Material: Titanium alloy uns r56400 **Material Specification:** Ams 7461 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-01-315-4889

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0