NSN 5306-01-315-5529

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-315-5529 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.391 inches and 0.485 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.312 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.060 inches **Hole Diameter:** Between 0.060 inches and 0.070 inches **First Diameter From Head:** Between 0.222 inches and 0.232 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.025 inches and 0.099 inches **Thread Diameter:** 0.250 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Double hexagon longitudinal hole **Externally Relieved Body Diameter Quantity: Special Features:** Heat treated per pwa 586-3 except head Material:

Nickel alloy 718

Material Specification:

Pwa 96 cagec 77445 mfr ref single material response or ams 5662 assn standard single material response

NSN 5306-01-315-5529

Externally Relieved Body Bolt - Page 2 of 2



| Thread Series Designator: |
|---------------------------|
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0