

View Online at <https://aerobasegroup.com/nsn/5306-01-315-5529>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.391 inches and 0.485 inches

**Fastener Length:**

Between 0.490 inches and 0.510 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.293 inches and 0.313 inches

**Width Between Flats:**

0.312 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

0.060 inches

**Hole Diameter:**

Between 0.060 inches and 0.070 inches

**First Diameter From Head:**

Between 0.222 inches and 0.232 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.025 inches and 0.099 inches

**Thread Diameter:**

0.250 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Heat treated per pwa 586-3 except head

**Material:**

Nickel alloy 718

**Material Specification:**

Pwa 96 cagec 77445 mfr ref single material response or ams 5662 assn standard single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0