NSN 5306-01-316-7984

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-316-7984 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.865 inches and 1.028 inches **Fastener Length:** Between 1.615 inches and 1.635 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.328 inches and 0.348 inches Width Between Flats: 0.375 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** 0.070 inches **First Diameter From Head:** Between 0.280 inches and 0.290 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.607 inches and 0.750 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity: Special Features:** Grip and bearing surface of head 32 micro inches; point and bearing surface heat treated per pwa 586-3 cagec 77445 Material: Nickel alloy uns n07001 **Material Specification:** Ams 7477 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5306-01-316-7984

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0