

View Online at <https://aerobasegroup.com/nsn/5306-01-316-8947>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.514 inches

Fastener Length:

Between 1.635 inches and 1.655 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.373 inches and 0.393 inches

Width Between Flats:

0.438 inches

Extended Washer Diameter:

Between 0.552 inches and 0.572 inches

Extended Washer Thickness:

0.092 inches

Hole Diameter:

Between 0.250 inches and 0.270 inches

First Diameter From Head:

Between 0.307 inches and 0.311 inches

Second Diameter From Head:

0.421 inches

Third Diameter From Head:

Between 0.307 inches and 0.311 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.240 inches and 0.260 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.645 inches and 0.655 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 1.121 inches and 1.141 inches

End Application:

F100pw0229 engine/core

Thread Diameter:

0.375 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Double hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

2

Material:

Cobalt alloy

Material Specification:

Ams 7475 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0