

View Online at <https://aerobasegroup.com/nsn/5306-01-317-2652>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.656 inches

Fastener Length:

Between 1.892 inches and 1.982 inches

Head Style:

Hexagon

Head Height:

0.312 inches

Width Between Flats:

0.562 inches

Shoulder Diameter:

0.405 inches first shoulder and 0.406 inches first shoulder

Shoulder Length:

1.251 inches first shoulder and 1.311 inches first shoulder

Hole Diameter:

Between 0.060 inches and 0.068 inches

Thread Diameter:

0.375 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Hardness Rating:

240.0 brinell standard and 280.0 brinell standard

Hole Configuration Style:

Hexagon flats

Shoulder Shape:

Round first shoulder

Special Features:

Before lubricating oil protective coating per dod-p-16232 ty m cl 4

Material:

Steel

Surface Treatment:

Lubricant

Surface Treatment Specification:

Mil-I-3150 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-I-3150 spec.