NSN 5306-01-317-4007

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-317-4007

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.632 inches and 0.682 inches
Fastener Length:
Between 1.767 inches and 1.797 inches
Head Style:
Double hexagon extended washer
Head Height:
0.388 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Extended Washer Diameter:
Between 0.639 inches and 0.649 inches
Extended Washer Thickness:
0.091 inches
Hole Diameter:
Between 0.050 inches and 0.060 inches
Grip Diameter:
Between 0.3735 inches and 0.3745 inches
Thread Diameter:
0.375 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
200000 pounds per square inch
Hole Configuration Style:
Double hexagon longitudinal hole

Material:

Iron alloy 660

Material Specification:

Ams 5737 assn standard single material response

Surface Treatment:

Cadmium and chromate

NSN 5306-01-317-4007

Shear Bolt - Page 2 of 2



Surface Treatment Speci

Qq-p-416 type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0