## NSN 5306-01-317-5133

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-317-5133



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.900 inches and 0.950 inches

### Fastener Length:

Between 1.785 inches and 1.815 inches

#### Head Style:

Spline extended washer

## Head Height:

Between 0.552 inches and 0.572 inches

## **Extended Washer Diameter:**

Between 1.153 inches and 1.163 inches

## **Extended Washer Thickness:**

Between 0.080 inches and 0.100 inches

#### **Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

#### Head Minor Diameter:

Between 0.673 inches and 0.688 inches

## Thread Diameter:

0.625 inches

Grip Length:

Between 0.865 inches and 0.885 inches

## Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

## Surface Finish:

32.0 microinches grip

#### Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

## Thread Series Designator:

Unjf

## Shelf Life:

N/a

# NSN 5306-01-317-5133

Shear Bolt - Page 2 of 2



---

Demilitarization:

No

Fiig:

A003b0

