## NSN 5306-01-317-9018

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-317-9018 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.215 inches **Fastener Length:** Between 0.445 inches and 0.455 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: 0.435 inches **First Diameter From Head:** Between 0.190 inches and 0.194 inches **Second Diameter From Head:** Between 0.249 inches and 0.250 inches **Third Diameter From Head:** Between 0.190 inches and 0.194 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.072 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.126 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.236 inches **End Application:** F100pw0229 engine/core mod **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 3 Material: Nickel alloy **Material Specification:** Pwa 96 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-317-9018

Externally Relieved Body Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0