

View Online at <https://aerobasegroup.com/nsn/5306-01-318-3016>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.334 inches

**Fastener Length:**

1.298 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

0.219 inches

**Width Between Flats:**

0.558 inches

**Extended Washer Diameter:**

0.558 inches

**Extended Washer Thickness:**

Between 0.015 inches and 0.025 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.116 inches first hole

**First Diameter From Head:**

Between 0.304 inches and 0.314 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.094 inches and 0.114 inches

**End Application:**

1560-00-460-1523 and 1560-00-460-1524 on f-111t acft

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

46.0 rockwell c and 50.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.105 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Externally relieved area is between grip and threads; grip is 0.860 in. Lg x 0.4360/0.4370 in. Dia

**Material:**

Stainless steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Qq-c-320, class ii federal specification single treatment response grip

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0