

View Online at <https://aerobasegroup.com/nsn/5306-01-318-3016>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.334 inches

Fastener Length:

1.298 inches

Head Style:

Hexagon extended washer

Head Height:

0.219 inches

Width Between Flats:

0.558 inches

Extended Washer Diameter:

0.558 inches

Extended Washer Thickness:

Between 0.015 inches and 0.025 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

First Diameter From Head:

Between 0.304 inches and 0.314 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.094 inches and 0.114 inches

End Application:

1560-00-460-1523 and 1560-00-460-1524 on f-111t acft

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.105 inches first hole

Externally Relieved Body Diameter Quantity:

1

Special Features:

Externally relieved area is between grip and threads; grip is 0.860 in. Lg x 0.4360/0.4370 in. Dia

Material:

Stainless steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-c-320, class ii federal specification single treatment response grip

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0