## NSN 5306-01-318-7473

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-318-7473 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.373 inches **Fastener Length:** Between 1.160 inches and 1.180 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.045 inches **First Diameter From Head:** Between 0.2465 inches and 0.2475 inches **Second Diameter From Head:** Between 0.130 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.745 inches and 0.755 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.797 inches **End Application:** F100pw0229 engine **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Head hole 0.090-0.110 in. Diameter x 0.128 in. Nom deep Material: Nickel alloy **Material Specification:** 

Ams 7471 assn standard single material response **Thread Series Designator:** Unjf

## NSN 5306-01-318-7473

Externally Relieved Body Bolt - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0