## NSN 5306-01-318-9533

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-318-9533 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.870 inches **Fastener Length:** Between 3.710 inches and 3.750 inches **Head Style:** Hexagon **Head Height:** Between 0.381 inches and 0.421 inches Width Between Flats: 1.000 inches **Shoulder Diameter:** 0.681 inches first shoulder and 0.683 inches first shoulder **Shoulder Length:** 2.459 inches fourth shoulder **Thread Diameter:** 0.625 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 180000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 **Material Specification:** Mil-s-5000 military specification single material response **Surface Treatment:** Phosphate manganese **Surface Treatment Specification:** Dod-p-16232 tym cl4 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: **Unit Of Measure:** 

N/a **Demilitarization:** No

## NSN 5306-01-318-9533

Shoulder Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.