NSN 5306-01-319-1434

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-1434 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.263 inches **Fastener Length:** Between 0.760 inches and 0.770 inches **Head Style:** Round w/wrench flats **Head Diameter:** Between 1.000 inches and 1.020 inches **Head Height:** Between 0.030 inches and 0.040 inches Width Between Flats: Between 0.331 inches and 0.341 inches First Diameter From Head: Between 0.240 inches and 0.246 inches **Second Diameter From Head:** Between 0.120 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.450 inches and 0.460 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.502 inches **End Application:** F100pw0229 engine/aug mod **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Nickel alloy **Material Specification:** Ams 5665 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5306-01-319-1434

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0