## NSN 5306-01-319-2108

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-2108

**Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.510 inches and 0.560 inches **Fastener Length:** Between 0.770 inches and 0.800 inches **Head Style:** Spline extended washer **Head Height:** Between 0.240 inches and 0.260 inches **Extended Washer Diameter:** Between 0.460 inches and 0.470 inches **Extended Washer Thickness:** Between 0.026 inches and 0.046 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Head Minor Diameter:** Between 0.235 inches and 0.250 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 260000 pounds per square inch **Hardness Rating:** 51.0 rockwell c and 54.0 rockwell c Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837 type 2, cl 2 federal specification single treatment response

Unjf

Shelf Life:

**Thread Series Designator:** 

N/a

## NSN 5306-01-319-2108

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.