## NSN 5306-01-319-2113

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-2113

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.345 inches and 0.395 inches Fastener Length: Between 0.667 inches and 0.697 inches Head Style: Dished hexagon Head Height: Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch
Thread Direction: Right-hand Thread Length: Between 0.345 inches and 0.395 inches Fastener Length: Between 0.667 inches and 0.697 inches Head Style: Dished hexagon Head Height: Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Right-hand Thread Length: Between 0.345 inches and 0.395 inches Fastener Length: Between 0.667 inches and 0.697 inches Head Style: Dished hexagon Head Height: Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Thread Length: Between 0.345 inches and 0.395 inches Fastener Length: Between 0.667 inches and 0.697 inches Head Style: Dished hexagon Head Height: Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Between 0.345 inches and 0.395 inches  Fastener Length:  Between 0.667 inches and 0.697 inches  Head Style:  Dished hexagon  Head Height:  Between 0.125 inches and 0.140 inches  Width Between Flats:  Between 0.429 inches and 0.439 inches  Grip Diameter:  Between 0.2485 inches and 0.2495 inches  Thread Diameter:  0.250 inches  Grip Length:  Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):
Fastener Length: Between 0.667 inches and 0.697 inches  Head Style: Dished hexagon  Head Height: Between 0.125 inches and 0.140 inches  Width Between Flats: Between 0.429 inches and 0.439 inches  Grip Diameter: Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Between 0.667 inches and 0.697 inches  Head Style: Dished hexagon  Head Height: Between 0.125 inches and 0.140 inches  Width Between Flats: Between 0.429 inches and 0.439 inches  Grip Diameter: Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Head Style: Dished hexagon  Head Height: Between 0.125 inches and 0.140 inches  Width Between Flats: Between 0.429 inches and 0.439 inches  Grip Diameter: Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Dished hexagon  Head Height:  Between 0.125 inches and 0.140 inches  Width Between Flats:  Between 0.429 inches and 0.439 inches  Grip Diameter:  Between 0.2485 inches and 0.2495 inches  Thread Diameter:  0.250 inches  Grip Length:  Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):
Head Height: Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Between 0.125 inches and 0.140 inches  Width Between Flats: Between 0.429 inches and 0.439 inches  Grip Diameter: Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches Thread Diameter: 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Between 0.429 inches and 0.439 inches  Grip Diameter:  Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length:  Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):
Grip Diameter:  Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length:  Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Between 0.2485 inches and 0.2495 inches  Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
Thread Diameter: 0.250 inches  Grip Length: Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi): 28  Min. Tensile Strength (psi):
0.250 inches  Grip Length:  Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):
Grip Length: Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
Between 0.302 inches and 0.322 inches  Thready Qty Per Inch (tpi):  28  Min. Tensile Strength (psi):
Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi):
28 Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Nas 4006 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6404 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5306-01-319-2113

Shear Bolt - Page 2 of 2



em			

No

Fiig:

A003b0