NSN 5306-01-319-2116



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-319-2116 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.320 inches and 0.370 inches **Fastener Length:** Between 0.580 inches and 0.610 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas 4006 assn standard single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6803 professional/industrial association standard Shelf Life:

--

N/a

Unit Of Measure:

NSN 5306-01-319-2116

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0