## NSN 5306-01-319-2428

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-2428

view Online at https://aerobasegroup.com/hish/5500-01-515-2420
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.227 inches and 1.277 inches
Fastener Length:
Between 7.675 inches and 7.705 inches
Head Style:
Dished hexagon
Head Height:
Between 0.312 inches and 0.327 inches
Width Between Flats:
Between 0.928 inches and 0.940 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.6235 inches and 0.6240 inches
Thread Diameter:
0.625 inches
Grip Length:
Between 6.428 inches and 6.448 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon flats
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6410 professional/industrial association standard

## NSN 5306-01-319-2428

Shear Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0