## NSN 5306-01-319-3624

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-3624 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.310 inches **Fastener Length:** Between 0.552 inches and 0.572 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.328 inches and 0.348 inches Width Between Flats: 0.375 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** 0.075 inches **First Diameter From Head:** Between 0.3105 inches and 0.3115 inches **Second Diameter From Head:** Between 0.175 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.185 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.252 inches **End Application:** F100pw0229 engine/core mod **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Special Features:** Head hole 0.196-0.216 in. Diameter x 0.170 in. Nom deep Material:

Nickel alloy

**Material Specification:** 

Pwa 96 mfr ref single material response

**Surface Treatment Specification:** 

Pwa 36545-3 mfr ref single treatment response threads

## NSN 5306-01-319-3624

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0