

View Online at <https://aerobasegroup.com/nsn/5306-01-319-8647>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.271 inches

Fastener Length:

1.120 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.172 inches and 0.204 inches

Width Between Flats:

0.497 inches

Extended Washer Diameter:

0.497 inches

Extended Washer Thickness:

Between 0.015 inches and 0.025 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

First Diameter From Head:

Between 0.3735 inches and 0.3745 inches

Second Diameter From Head:

Between 0.241 inches and 0.251 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.745 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

0.849 inches

End Application:

Spike assembly. P/n's 12p12010-807, -808 for f-111t acft

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.960 inches first hole

Externally Relieved Body Diameter Quantity:

1

Material:

Stainless steel

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium head

Surface Treatment Specification:

Qq-c-320, class 2 federal specification single treatment response grip

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0