

View Online at <https://aerobasegroup.com/nsn/5306-01-319-8647>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.271 inches

**Fastener Length:**

1.120 inches

**Head Style:**

Hexagon extended washer

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

0.497 inches

**Extended Washer Diameter:**

0.497 inches

**Extended Washer Thickness:**

Between 0.015 inches and 0.025 inches

**Shank Unthreaded Hole Diameter:**

0.066 inches first hole and 0.086 inches first hole

**First Diameter From Head:**

Between 0.3735 inches and 0.3745 inches

**Second Diameter From Head:**

Between 0.241 inches and 0.251 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.745 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.849 inches

**End Application:**

Spike assembly. P/n's 12p12010-807, -808 for f-111t acft

**Thread Diameter:**

0.3125 inches

**Thready Qty Per Inch (tpi):**

24

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.960 inches first hole

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Stainless steel

**Material Specification:**

Ams 6487 assn standard single material response

**Surface Treatment:**

Cadmium head

**Surface Treatment Specification:**

Qq-c-320, class 2 federal specification single treatment response grip

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0