# NSN 5306-01-319-9442

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-319-9442

### Thread Class:

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.413 inches and 0.463 inches

#### Fastener Length:

Between 1.923 inches and 1.953 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.156 inches and 0.171 inches

#### Width Between Flats:

Between 0.492 inches and 0.502 inches

#### Grip Diameter:

Between 0.3115 inches and 0.3120 inches

#### **Thread Diameter:**

0.312 inches

## Grip Length:

Between 1.490 inches and 1.510 inches

### Thready Qty Per Inch (tpi):

24

# Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

Nas 4006 assn standard single treatment response

# **Thread Series Designator:**

Unjf

## **Specification Data:**

80205-nas6405 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5306-01-319-9442

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

