NSN 5306-01-320-0609

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-320-0609 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.361 inches **Fastener Length:** Between 1.200 inches and 1.220 inches **Head Style:** Tee no. 6 **Head Height:** Between 0.090 inches and 0.110 inches **Head Length:** Between 0.550 inches and 0.570 inches Width Between Flats: 0.435 inches First Diameter From Head: 0.310 inches **Second Diameter From Head:** Between 0.185 inches and 0.195 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.782 inches and 0.792 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.849 inches **End Application:** F100pw0229 engine/aug mod **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity: Chamfer Angle:** Between 44.0 degrees and 46.0 degrees Material: Nickel alloy **Material Specification:** Ams 7466 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-01-320-0609

Externally Relieved Body Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0