

View Online at <https://aerobasegroup.com/nsn/5306-01-320-1332>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.433 inches

**Fastener Length:**

Between 1.670 inches and 1.690 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.293 inches and 0.313 inches

**Width Between Flats:**

0.3125 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.448 inches

**Extended Washer Thickness:**

0.065 inches

**First Diameter From Head:**

Between 0.308 inches and 0.310 inches

**Second Diameter From Head:**

Between 0.194 inches and 0.198 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 1.180 inches and 1.190 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.247 inches

**End Application:**

F100pw0229 engine

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Center head hole 0.140/0.160 in. Diameter x 0.135 in. Nom deep

**Material:**

Stainless steel

**Material Specification:**

Ams 7477 assn standard single material response and pwa-s-7477, cage77445 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0