## NSN 5306-01-320-1333

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-320-1333 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.433 inches **Fastener Length:** Between 2.375 inches and 2.395 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.293 inches and 0.313 inches Width Between Flats: 0.3125 inches **Extended Washer Diameter:** Between 0.428 inches and 0.448 inches **Extended Washer Thickness:** 0.065 inches **First Diameter From Head:** Between 0.308 inches and 0.310 inches **Second Diameter From Head:** Between 0.194 inches and 0.198 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.885 inches and 1.895 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.952 inches **End Application:** F100pw0229 engine **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Center head hole 0.140/0.160 in. Diameter x 0.135 in. Nom deep Material: Stainless steel **Material Specification:** Ams 7477 assn standard single material response and pwa-s-7477, cage77445 mfr ref single material response **Thread Series Designator:** 

Unjf

## NSN 5306-01-320-1333

Externally Relieved Body Bolt - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0