## NSN 5306-01-320-1452

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-320-1452 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.372 inches **Fastener Length:** Between 0.865 inches and 0.885 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.248 inches and 0.268 inches Width Between Flats: 0.250 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** 0.045 inches **First Diameter From Head:** Between 0.2435 inches and 0.2480 inches **Second Diameter From Head:** Between 0.130 inches and 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.454 inches and 0.458 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.503 inches **End Application:** F100pw0229 engine **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 34.0 rockwell c and 44.0 rockwell c **Externally Relieved Body Diameter Quantity: Special Features:** Center head hole 0.090/0.110 in. Diameter x 0.128 in. Nom deep

Material:

Nickel alloy

**Material Specification:** 

Ams 7471 assn standard single material response

## NSN 5306-01-320-1452

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0