NSN 5306-01-320-1453

Externally Relieved Body Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-320-1453 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.253 inches |
| Fastener Length: |
| 1.212 inches |
| Head Style: |
| Square |
| Head Height: |
| Between 0.125 inches and 0.135 inches |
| Width Between Flats: |
| 0.360 inches |
| First Diameter From Head: |
| Between 0.2500 inches and 0.2505 inches |
| Second Diameter From Head: |
| Between 0.130 inches and 0.140 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.910 inches and 0.914 inches |
| Distance From Largest Bearing Surface Of Head To End Of Second Diameter: |
| 0.959 inches |
| End Application: |
| F100pw0229 engine |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Nickel alloy |
| Material Specification: |
| Ams 7467 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5306-01-320-1453

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0