

View Online at <https://aerobasegroup.com/nsn/5306-01-321-1047>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.215 inches

Fastener Length:

Between 0.470 inches and 0.480 inches

Head Style:

Hexagon extended washer

Head Height:

Between 0.195 inches and 0.205 inches

Width Between Flats:

0.497 inches

Extended Washer Diameter:

Between 0.460 inches and 0.510 inches

Extended Washer Thickness:

Between 0.006 inches and 0.016 inches

First Diameter From Head:

Between 0.247 inches and 0.251 inches

Second Diameter From Head:

Between 0.317 inches and 0.319 inches

Third Diameter From Head:

Between 0.247 inches and 0.251 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.080 inches and 0.090 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.115 inches and 0.125 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

Between 0.255 inches and 0.265 inches

End Application:

F100pw0229 engine

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

2

Material:

Nickel alloy

Material Specification:

Pwa96, cage77445 mfr ref single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0