NSN 5306-01-322-2891



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-01-322-2891 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.910 inches **Fastener Length:** Between 1.208 inches and 1.238 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.470 inches and 0.490 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.133 inches **Hole Diameter:** 0.055 inches **Grip Diameter:** 0.313 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 0.5605 inches and 0.5615 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 200000 pounds per square inch **Hole Configuration Style:** Double hexagon longitudinal hole **Surface Finish:** 32.0 microinches threads

Surface Finish
32.0 microinch
Color:
Green threads
Material:
Iron alloy 660

NSN 5306-01-322-2891

Shear Bolt - Page 2 of 2

No Fiig: A003b0



Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: