# NSN 5306-01-322-2909

U Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-322-2909

## Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

1.500 inches

### Shank Unthreaded Hole Diameter:

0.190 inches all holes

# Distance From Inside Center Of Bend To Bolt End:

11.880 inches

## Inside Distance Between Shanks:

3.000 inches

**Thread Diameter:** 

0.190 inches

Thready Qty Per Inch (tpi):

20

## Distance From Threaded End To Shank Hole Center:

0.620 inches all holes

### Material:

Steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp

1023 or steel comp 1015

# Surface Treatment:

Chromate zinc

#### Surface Treatment Specification:

Mil-p-8585 military specification single treatment response

#### Style Designator:

Square bend

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

--

```
Demilitarization:
```

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-p-8585 spec.