## NSN 5306-01-322-6975

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-322-6975



### **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** 0.338 inches Fastener Length: Between 0.448 inches and 0.478 inches **Head Style:** Dished hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches Hole Diameter: Between 0.046 inches and 0.056 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.115 inches and 0.135 inches **Hole Quantity:** 3 Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hole Configuration Style: Hexagon corners Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response

#### Thread Series Designator:

Unjf

# NSN 5306-01-322-6975

Shear Bolt - Page 2 of 2



**Specification Data:** 

80205-nas1953 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A003b0