

View Online at <https://aerobasegroup.com/nsn/5306-01-323-7927>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.769 inches

**Shank Length:**

0.880 inches

**Eye Stock Diameter:**

1.385 inches

**Shoulder Diameter:**

Between 0.743 inches and 0.748 inches

**Shoulder Length:**

1.500 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Ring Stock Diameter:**

0.645 inches

**Ring Inside Diameter:**

2.500 inches

**Thread Diameter:**

0.562 inches

**Thread Qty Per Inch (tpi):**

18

**Hardness Rating:**

35.0 rockwell c and 39.0 rockwell c

**Distance From Threaded End To Shank Hole Center:**

0.218 inches first hole

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8735 or steel comp 8740 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification single treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0