

View Online at <https://aerobasegroup.com/nsn/5306-01-323-9085>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.250 inches and 0.260 inches

Fastener Length:

Between 1.190 inches and 1.210 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.250 inches and 0.270 inches

Width Between Flats:

0.3125 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

Between 0.060 inches and 0.070 inches

First Diameter From Head:

Between 0.181 inches and 0.183 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.855 inches

End Application:

F100pw0229 engine

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Double hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

1

Special Features:

Threaded area is next to head; ex-ternally relieved area is a dowl-like projection between threads and tip; center hole at top of head is 0.140/0.160in. Diameter x 0.167 in. Nom deep

Material:

Titanium alloy

Material Specification:

Ams 7461 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0