NSN 5306-01-323-9204

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-323-9204 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.452 inches **Fastener Length:** Between 2.755 inches and 2.775 inches **Head Style:** Tee no. 6 **Head Height:** Between 0.090 inches and 0.100 inches **Head Length:** Between 0.480 inches and 0.500 inches Width Between Flats: 0.375 inches **Shoulder Diameter:** 0.248 inches first shoulder and 0.249 inches first shoulder **Shoulder Length:** 1.895 inches first shoulder and 1.905 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.065 inches first hole and 0.072 inches first hole **End Application:** F100pw0229 engine **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Distance From Head Largest Bearing Surface To Shank Hole Center: 2.590 inches first hole **Chamfer Angle:** Between 44.0 degrees and 46.0 degrees **Shoulder Shape:** Round first shoulder Material: Nickel alloy **Material Specification:** Ams 7471 assn standard single material response **Thread Series Designator:**

Unjf

Shelf Life:

N/a

NSN 5306-01-323-9204

Shoulder Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0