NSN 5306-01-324-2583

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-324-2583

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.041 inches
Fastener Length:
Between 1.088 inches and 1.118 inches
Head Style:
Hexagon
Head Height:
Between 0.375 inches and 0.395 inches
Width Between Flats:
Between 1.052 inches and 1.064 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
Thread Diameter:
0.750 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches grip
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:

Qq-p-416, ty2 cl2 federal specification single treatment response

NSN 5306-01-324-2583

Shear Bolt - Page 2 of 2

A003b0



Thread Series Designator:
Unjf
Specification Data:
80205-nas1312 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: