Externally Relieved Body Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-01-324-6711



| 20 | |
|--------------------|---|
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| | hes and 1.065 inches |
| Fastener Length: | |
| | hes and 2.515 inches |
| Head Style: | |
| Double hexagon | |
| Head Height: | |
| 0.580 inches | |
| Width Between F | ats: |
| Between 1.052 inc | hes and 1.064 inches |
| First Diameter Fre | om Head: |
| Between 0.660 inc | hes and 0.665 inches |
| Distance From La | rrgest Bearing Surface Of Head To End Of First Diameter: |
| Between 1.420 inc | hes and 1.480 inches |
| Point Style: | |
| Flat | |
| Thread Diameter: | |
| 0.750 inches | |
| Features Provide | d: |
| Finished head | |
| Thready Qty Per | nch (tpi): |
| 16 | |
| Min. Tensile Stre | ngth (psi): |
| 220000 pounds pe | r square inch |
| Externally Reliev | ed Body Diameter Quantity: |
| 1 | |
| Material: | |
| Nickel alloy 718 | |
| Material Specifica | ition: |
| Ams 5662 assn sta | andard single material response or ams 5663 assn standard single material response or asm 5664 assn standard si |
| material response | |
| Thread Series De | signator: |
| Unjf | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 5306-01-324-6711

Externally Relieved Body Bolt - Page 2 of 2

Fiig: A003b0

