

View Online at <https://aerobasegroup.com/nsn/5306-01-324-6713>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.770 inches

Fastener Length:

Between 2.080 inches and 2.120 inches

Head Style:

Hexagon

Head Height:

0.300 inches

Width Between Flats:

Between 0.742 inches and 0.752 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

1.330 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 48.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.833 inches first hole

Material:

Steel uns k23080

Material Specification:

Ams 6411 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ps13102 cl b, cagec 76301 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0