

View Online at <https://aerobasegroup.com/nsn/5306-01-324-8859>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.614 inches

**Fastener Length:**

Between 1.599 inches and 1.629 inches

**Head Style:**

Spline extended washer

**Head Height:**

Between 0.327 inches and 0.347 inches

**Extended Washer Diameter:**

Between 0.601 inches and 0.701 inches

**Extended Washer Thickness:**

Between 0.044 inches and 0.064 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole and 0.111 inches first hole

**Head Minor Diameter:**

Between 0.423 inches and 0.438 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 0.990 inches and 1.010 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.376 inches first hole and 1.416 inches first hole

**Material:**

Steel comp xm-13

**Material Specification:**

Ams 5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0