## **NSN 5306-01-325-3863** Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-325-3863
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.444 inches and 0.494 inches
Fastener Length:
Between 1.569 inches and 1.589 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.115 inches and 1.135 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5306-01-325-3863

Shear Bolt - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.