

View Online at <https://aerobasegroup.com/nsn/5306-01-325-5942>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.600 inches

Fastener Length:

2.620 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.900 inches

Head Height:

0.330 inches

Width Between Flats:

1.680 inches

Shoulder Diameter:

Between 1.2489 inches and 1.2494 inches

Shoulder Length:

1.140 inches

Shank Unthreaded Hole Diameter:

0.139 inches and 0.145 inches first hole

Concentric Hole Depth:

1.960 inches

Counterbore Diameter:

Between 0.8750 inches and 0.8759 inches

Counterbore Depth:

1.300 inches

Concentric Hole Diameter:

Between 0.561 inches and 0.570 inches

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

200000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.600 inches first hole

Special Features:

Groove on 0.930-0.940 in diameter x .120 wide located o relief; hex between relief and threads 0.130 in dia.; surface finish on all shoulders and relief 32.0

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Style Designator:

Counterbore unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.