NSN 5306-01-326-0527

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-326-0527

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.468 inches
Fastener Length:
Between 0.953 inches and 0.983 inches
Head Style:
Spline extended washer
Head Height:
Between 0.240 inches and 0.260 inches
Extended Washer Diameter:
Between 0.460 inches and 0.470 inches
Extended Washer Thickness:
Between 0.182 inches and 0.192 inches
Hole Diameter:
Between 0.082 inches and 0.092 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Head Minor Diameter:
Between 0.318 inches and 0.324 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Passivate

NSN 5306-01-326-0527

Shear Bolt - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0