## NSN 5306-01-326-2689

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-326-2689

Thread Class:
3a Thread Direction
Thread Direction:
Right-hand
Thread Length: 0.425 inches
Fastener Length: Between 1.160 inches and 1.190 inches
Head Style:
Dished hexagon Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.740 inches and 0.760 inches
Hole Quantity:
3
G Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Og-p-116 tv2 cl2 federal specification single treatment response

Qq-p-416 ty2 cl2 federal specification single treatment response

## NSN 5306-01-326-2689

Shear Bolt - Page 2 of 2



**Thread Series Designator:** 

Unjf

Specification Data:

80205-nas6704 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0