## NSN 5306-01-326-3403

Shear Bolt - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5306-01-326-3403

| Thread Class:  |
|--|
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.370 inches   |
| Fastener Length:   |
| Between 0.480 inches and 0.510 inches  |
| Head Style:  |
| Dished hexagon   |
| Head Height:   |
| Between 0.125 inches and 0.140 inches  |
| Width Between Flats:   |
| Between 0.429 inches and 0.439 inches  |
| Locking Feature:   |
| Patch threads  |
| Grip Diameter:   |
| Between 0.2490 inches and 0.2495 inches  |
| Thread Diameter:   |
| 0.250 inches   |
| Grip Length:   |
| Between 0.115 inches and 0.135 inches  |
| Thready Qty Per Inch (tpi):  |
| 28   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Surface Finish:  |
| 32.0 microinches threads   |
| Material:  |
| Titanium alloy uns r56400 fastener   |
| Material Specification:  |
| Ams4928 assn standard single material response fastener or ams4967 assn standard single material response fastener |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas6404 professional/industrial association standard   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
|  |

## NSN 5306-01-326-3403

Shear Bolt - Page 2 of 2

Fiig: A003b0

