NSN 5306-01-326-4913

Machine Bolt - Page 1 of 2

Thread Class:

silver



View Online at https://aerobasegroup.com/nsn/5306-01-326-4913

| 3a |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.750 inches and 0.810 inches |
| Fastener Length: |
| 2.000 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.300 inches |
| Width Between Flats: |
| 0.312 inches |
| Extended Washer Diameter: |
| 0.438 inches |
| Extended Washer Thickness: |
| 0.060 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 1.190 inches and 1.250 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Surface Finish: |
| 32.0 microinches grip |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response |
| Precious Material And Location: |

NSN 5306-01-326-4913

Machine Bolt - Page 2 of 2

A003b0



| Precious Material: |
|--|
| Silver |
| Surface Treatment: |
| Silver |
| Surface Treatment Specification: |
| Ams 2411 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |