## NSN 5306-01-327-0366

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-327-0366 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.599 inches **Fastener Length:** 1.286 inches **Head Style:** Double hexagon extended washer **Head Height:** 0.348 inches Width Between Flats: 0.375 inches **Extended Washer Diameter:** Between 0.521 inches and 0.531 inches **Extended Washer Thickness:** 0.082 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.677 inches and 0.697 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 43.0 rockwell c **Surface Finish:** 32.0 microinches grip Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf

Unji

Shelf Life:

N/a

## NSN 5306-01-327-0366

Shear Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0