## NSN 5306-01-327-0369

Shear Bolt - Page 1 of 2





### Thread Class: 3a

Thread Direction:

Right-hand

#### Thread Length:

0.370 inches

#### Fastener Length:

Between 0.917 inches and 0.947 inches

#### Head Style:

Dished hexagon

#### Head Height:

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Locking Feature:

Patch threads or strip threads or pellet threads

#### Grip Diameter:

Between 0.2490 inches and 0.2495 inches

#### **Thread Diameter:**

0.250 inches

#### Grip Length:

Between 0.552 inches and 0.572 inches

#### Thready Qty Per Inch (tpi):

28

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Titanium alloy uns r56400 fastener

#### **Material Specification:**

Ams 4928 assn standard single material response fastener or ams 4967 assn standard single material response fastener

#### **Thread Series Designator:**

Unjf

#### **Specification Data:**

80205-nas6404 professional/industrial association standard

#### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5306-01-327-0369

Shear Bolt - Page 2 of 2

Fiig: A003b0

