## NSN 5306-01-327-5684

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-327-5684

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.425 inches
Fastener Length:
Between 0.722 inches and 0.752 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Special Features:
Paint threads only rer
Color:
Red threads
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Ams 4928 assn standard single treatment response or ams 4967 assn standard single treatment response
Thread Series Designator:
Unjf

## NSN 5306-01-327-5684

Shear Bolt - Page 2 of 2



Specification Data	a
--------------------	---

80205-nas6804 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0